



**DECLARATION OF PERFORMANCE**  
**Nº30-PCM-202502**

Name and Identification code:

Product: **SCRAPED**

Código: SEE TRACEABILITY CODE ON PRODUCT

Name and address of the Manufacturer

Name: **PRODUCTOS CERÁMICOS MORA S.L.**

Address: **CARRETERA ANTIGUA MADRID-TOLEDO Km 38,400 CP:45200 ILLESCAS-TOLEDO**

Use: Slip brick for external and internal facade (EN 14411:2016)

System of Assessment and verification: **4**

Notified body: **30-PCM-202502** Performed initial inspection, continuous surveillance, assessment and evaluation of production control and issued

Evaluation System: **4**

**Declaration of Performance**

| DESIGNATION/CHARACTERISTICS |                  | DECLARATIONS         | TOLERANCES       | REQUERIMENTS STANDARD |
|-----------------------------|------------------|----------------------|------------------|-----------------------|
| Dimensions                  | Length (mm)      | 210                  | ±1.25% (máx 2mm) | UNE-EN ISO 10545-2    |
|                             | Heigth (mm)      | 65                   | ±1.25% (máx 2mm) |                       |
|                             | Width (mm)       | 14                   | ±10%             |                       |
| Straightness of sides       |                  | ±0.5%                |                  |                       |
| Rectangularity              |                  | ±1%                  |                  |                       |
| Curvature and Warpage       | Center Curvature |                      | ±0.5%            |                       |
|                             | Edge Curvature   |                      | ±0.5%            |                       |
|                             | Warpage          |                      | ±0.8%            |                       |
| Surface Quality             |                  | ≥95% free of defects |                  |                       |
| Water absorption            |                  | ≤6%                  |                  | UNE-EN ISO 10545-3    |
| Breaking Strenght           |                  | ≥1700 N              |                  | UNE-EN ISO 10545-4    |
| Flexural Strenght           |                  | ≥12 N/mm²            |                  |                       |
| Resistance to Deep Abrasion |                  | 950 mm³              |                  | UNE-EN ISO 10545-6    |
| Resistance to Thermal Shock |                  | MEETS SPECIFICATIONS |                  | UNE-EN ISO 10545-9    |
| Frost Resistance            |                  | MEETS SPECIFICATIONS |                  | UNE-EN ISO 10545-12   |

The performance of the product identified in this declaration is in accordance with the performance declared in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer indicated by name and address in this declaration.

Signed

Place and date of issue

Illescas (Toledo) a: 21-02-2025

